

Hisense

FANLESS POS TERMINAL DESIGNED FOR OPTIMUM PERFORMANCE



Hisense HK570e

2.42Ghz Quad Core
High Performance POS Terminal

New High
Performance
POS Terminal
4GB Memory
as Standard



• Sleek design that suites any restaurant environment.



• Powerful processor meets the demand of high inventory retail businesses.



Key Features

- Intel Bay Trail Quad Core J1900 2.42GHz. Fanless Processor.
- Projected Capacitive Touch (PCT).
- Die-Cast Aluminium Housing.
- Solid State Drive for Optimum Performance and Reliability.
- 15" True Flat Screen LCD with LED Back Lighting.
- Double Articulating Stand Folds Flat.


Hisense HK570e 2.42Ghz Quad Core High Performance POS Terminal

Key Features

- Intel Bay Trail Quad Core J1900 2.42GHz. Fanless Processor.
- Projected Capacitive Touch (PCT).
- Die-Cast Aluminium Housing.
- Solid State Drive for Optimum Performance and Reliability.
- 15" True Flat Screen LCD with LED Back Lighting.
- Double Articulating Stand Folds Flat.

Options

- 10" & 15" LCD Rear Customer Displays.
- VFD Rear Customer Display 2 x 20.
- MSR 3-Track / MSR + NFC.
- Fingerprint Module.



- Fast response PCT touch screen display.



- Fanless Intel Quad Core J1900 high performance processor.



- Numerous connectivity ports with excellent cable management.

HISENSE HK570E SPECIFICATION

Processor:	Intel Bay Trail Quad Core J1900 2.42GHz.	Serial Ports External:	COM1 / COM2 / COM3 COM3 (0V/5V/12V).
Cores/Threads:	Quad Core / 4 Threads.	Serial Ports Internal:	COM4 = For Rear VFD.
Cache Memory:	2GB.	Parallel Port:	Not Applicable.
Display LCD:	True Flat 15" LCD with LED Backlighting.	USB Ports:	Seven V2.0 / One V3.0 (Six Bottom / Two Back).
Resolution:	1024 x 768.	Cash Drawer Port:	RJ11 (24V) Maximum 1 Drawer Supports Open / Close.
Brightness:	420 CD/M ² .	HDMI Port:	Not Applicable.
Integrated Speakers:	Integrated 3 Watt Speakers.	LAN Port:	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111E.
Chipset (PCH):	CPU Integrated.	VGA Port:	One DB15F Display Port For Second LCD.
Touch - Panel:	Projected Capacitive Touch.	Audio Port:	One Line-Out.
Reliability:	Over 100 Million Touches.	Mic Port:	Not Applicable.
MCR:	Integrated USB Interface Triple Track MCR. Fingerprint Module.	Power Supply:	60W, 24V/2.5A External Power Adaptor 100-240V 50-60Hz.
Mass Storage Device:	64GB 2.5" Solid State Drive.	Current/Power Usage:	0.20A / 24W.
RAM Memory (1 Slot):	4GB SODIMM DDR3 (1333MHz) Expandable To 8GB.	Compatible O/S:	Windows 10IoT.
Video Memory:	Shared System Memory Up To 256MB.	Dimensions:	Overall: 396(W) x 330(H) x 248(D) mm.
Tilt Adjustment:	0° ~ 60° (Vertical).	Weight:	10.82 lbs.
		Safety and EMI:	FCC, Class-B / CE, Class-B / RoHS.

Hisense Also available

- Stylish, Space-Saving Rugged Tablets With Docking Stations.



YOUR DEALER IS:-

Hisense

Distributed in the UK & NI by YCR Distribution Ltd. 01924 438238. Whilst every effort has been made to provide current photographs, descriptions and specifications the manufacturers reserve the right to change specifications, illustrations, model number and appearance of any item without prior notifications and therefore will not be held responsible for any variations.