

Hisense

10 INCH RUGGED TABLET POS SYSTEM WITH OPTIONAL SMART DOCK



Hisense HM618

10.1" Rugged Tablet
High Performance POS Terminal



• Sleek design that suites any restaurant environment.



• Sleek design that suites any restaurant environment.

Key Features

- 10.1" Wide Screen.
- Bezel-Free, PCT Multi-Touch Screen.
- Standard Integrated Card Reader.
- Meets IP54 Standards.
- Sturdy Hand Strap Standard.

Options

- NFC Module.
- 1D Scanner Honeywell.
- 2D Scanner Honeywell.
- 4G Module.



Hisense HM618 10.1" Rugged Tablet

High Performance POS Terminal

Key Features

- 10.1" Wide Screen.
- Bezel-Free, PCT Multi-Touch Screen.
- Standard Integrated Card Reader.
- Meets IP54 Standards.
- Sturdy Hand Strap Standard.

Options

- NFC Module.
- 1D Scanner Honeywell.
- 2D Scanner Honeywell.
- 4G Module.



Note: Tablets do not communicate with Charging Dock or Smart Dock when removed.



- The multi-touch screen meets IP54 standards for dust & liquid.



- The HM618 has an integrated card reader as standard.



- The HM618 has a sturdy hand strap as standard.



HISENSE HM618 SPECIFICATION

Processor:	Intel Cherry Trail Z8350.	Tablet Dock Connection:	10 Pin Pogo Style Connector.
O/S:	Windows 10 IoT Enterprise LTSC.	Tablet I/O Interface:	Audio Jack / Nano SIM / Micro SD / Micro USB / USB V3.0 / DC Jack / Micro HDMI.
Display:	10.1" TFT LCD (LED Back-Light).	Charging Dock I/O:	5V Charging / Two USB V2.0.
Resolution:	1280 x 800.	Smart Dock I/O:	Cash Drawer / 24V Power / Two RS232C / Ethernet / Three USB V2.0.
Brightness:	Adjustable Up to 350 cd/m ² .	Power Supply:	Tablet/Charging Dock: 5V/4A External Power Adaptor 100-240V 50/60Hz.
Touch Panel:	True-Flat Projected Capacitive.	Temperature:	Smart Dock: 24V/3.75A External Power Adaptor 100-240V 50/60Hz.
Memory:	4GB RAM.	Humidity:	Operating: 32° F to 104° F (0° C to 40° C).
Storage:	64GB eMMC.	Dimensions:	Storage: -4° F to 140° F (-20° C to 60° C).
Camera:	Front: 2 Megapixel. Back: 5 Megapixel.	Weight:	Operating: 20% to 80% RH (Non-Condensing).
Wireless:	Wi-Fi: Dual Band WiFi (2.4G / 5G). Bluetooth: Integrated Bluetooth V4.1.		Storage: 10% to 90% RH (Non-Condensing).
Speaker:	Two Internal Speakers.		Tablet: 279 (W) x 178 (H) x 22 (D) mm.
Audio:	3.5mm Socket.		2.20 lbs.
MCR:	Standard Integrated Triple Track Card Reader.		
Battery:	Type: 3.7V 9000mAh. Life: 8 Hours with 50% Brightness.		

Hisense

Also available

- High Performance Rugged POS Terminals.



YOUR DEALER IS:-

Hisense

Distributed in the UK & NI by YCR Distribution Ltd. 01924 438238. Whilst every effort has been made to provide current photographs, descriptions and specifications the manufacturers reserve the right to change specifications, illustrations, model number and appearance of any item without prior notifications and therefore will not be held responsible for any variations.