

S A M 4 S T H E R M A L R E C E I P T P R I N T E R

SAM4s

Ellix-40 II

Thermal Receipt Printer

The innovative Ellix-40 II POS printer from Sam4s provides a unique LCD display that displays operator messages, errors and guides you through step by step program options.



- Easy Paper Loading & Jam Free/ Apply Auto Cutter.




- Aluminium Main Frame Structure for Robustness.



The Sam4s Ellix-40 II is easy to setup – easier to use and support.

SAM4s
Comes with an LCD Display Panel

Key Features - At A Glance





Ellix-40 II

Thermal Receipt Printer

- Energy Star Certified Reduces Energy Costs & Carbon Foot Print.
- Dual Interface Serial & USB as Standard.
- 270mm Per Second Print Speed.
- Drop & Print Loading.
- Prints Watermarks.
- Anti-Jam Technology.
- Stores User Defined Graphic Logos, Coupons or Advertising Messages.
- Support Barcode Printing Including QR Codes.
- Optional Splash Cover.
- Optional Kitchen Bell.



Features

- LCD Displays Operator Messages, Errors & Guides the Operator Through Setup & Option Selections.
- Aluminum Main Frame Insures Durability and Quiet Operation.
- Black/Red or Black/Blue Two-Colour Printing Available on Appropriate Paper.
- Accepts 2-1/4" (58mm) or 3-1/8" (80mm) Thermal Paper Rolls.
- Standard Near-End Paper Sensor.
- Guillotine Style, Jam-Free Auto-Cutter – Selectable Full or Partial Cut.
- Stores Up to 255 Images (384) KBytes in Non-Volatile Memory.
- Easy-To-Use Utilities Simplify Loading Images & Watermarks.
- Dual Interface – USB Interface is on the Main Board.

SAM4S ELLIX-40 SPECIFICATION

PRINTING METHOD		Direct Thermal Line Printing
PRINTING SPEED	Mono Paper 80mm	Maximum 270mm/Sec. (63 Lines/Sec)
	Mono Paper 58mm	Maximum 150mm/Sec. (36 Lines/Sec)
	Two Colour Paper	Maximum 100mm/Sec. (24 Lines/Sec).
RESOLUTION		180dpi (Dots Per Inch)
PRINTING WIDTH	Mono Paper 80mm	Maximum 72mm
	Mono Paper 58mm	48mm (Maximum 54mm)
PAPER	Loading Dimension Thickness	Drop-In Type Maximum 58/80 x 83mm 0.06 - 0.08mm
AUTO CUTTER		Guillotine Type (Jam Free)
MEMORY	PGM Memory	4 Megabyte
	Data Memory	8 Megabyte
	Data Buffer	64 KB
RELIABILITY	Mechanism (MCBF)/TPH/Auto Cutte	70,000,000 Lines/1 x 10 ⁸ Pulse, 150 Km/ 1,500,000 Cut
BARCODE		UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Code 128, ITF, CODABAR, PDF417, QR Code
DRIVER		Windows Driver, OPOS Driver, JPOS Driver, Mac Driver, Linux Driver
DRAWER PORT		2 Port (+24V)
INTERFACE		USB Only, USB + RS-232, USB + Parallel, USB + Ethernet, USB + Wi-Fi, USB + Bluetooth




- Built-In Wall Mount Capability (Option).



- Automatic Display Pivot Function When Wall Mounted.

Ports & Connectivity



- A:** Serial (Shown), Parallel, Ethernet, and USB (B) Interface Boards Available.
- B:** USB.
- C:** Cash Drawer (2 x Drawer 24v).
- D:** DC 24V Power-In.

YOUR LOCAL DEALER IS



Distributed in the UK & NI by YCR Distribution Ltd. 01924 438238. Whilst every effort has been made to provide current photographs, descriptions and specifications the manufacturers reserve the right to change specifications, illustrations, model number and appearance of any item without prior notifications and therefore will not be held responsible for any variations.